

DS-PDEBP1-EG2-WB

Wireless Portable Emergency Button

114-265

The DS-PDEBP1-EG2-WB portable emergency button is an easily controlled wireless product with high waterproof level. The button could be configured to panic mode or a medical mode by control panel. It is effective for emergency.



- Accidental press protection
- Fully remote configurable through App
- IP54 daily environment protection
- Frequency hopping against jamming for reliable transmission
- Optional lanyard and wristband accessory available

Specifications

	Model	DS-PDEBP1-EG2-WB
Features	Tamper-Proof	Support
	Signal strength indication	Support
Interface	Switch	1, Power switch
	Indicator	Flashing LED for Alarm(Red or Green)
RF Transmission	Wireless Technology	Tri-X Wireless Technology
	Two-way Wireless Communication	Support
	RF Frequency	433 MHz
	RF Range	800 m (open space)
	Wireless Security	AES-128 encryption
	Enrolling Methods	Power up, remote ID and QR code
Electrical characteristics	Frequency Hooping	Multichannel transmission
	Battery type	CR2032 x 1 (included)
General	Battery life span	3 years
	Application scenario	Indoor
	Dimension(WxHxD)	φ38 × 12 mm
	Weight	13.5g
	Operation temperature	-10 °C to 55 °C (14 °F to 131 °F)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Operation humidity	10% to 90%
	IP Rate	IP54

ORDERING INFORMATION

114-265

Hikvision AX PRO Series Portable Wireless Emergency Button



Innovative Electronic Solutions
www.ness.com.au



NSW Ph 02 8825 9222
sales@ness.com.au

VIC Ph 03 9875 6400
nessmelb@ness.com.au

QLD Ph 07 3399 4910
nessbris@ness.com.au

WA Ph 08 9328 2511
nessper@ness.com.au

SA Ph 08 8152 0000
adelaide@ness.com.au