


## DS-PK1-LRT-HWE/DS-PK1-LRT-HWB Wired keypad

114-501



The DS-PK1-LRT-HWE/DS-PK1-LRT-HWB wired keypad is an AX series keypad designed for AX hybrid pro control panel (DS-PHA48-EP, DS-PHA64-LP). The DS-PK1-LRT-HWE/DS-PK1-LRT-HWB supports built-in wireless transceiver and tag reader, which can work with keyfob and tag for arming/disarming.

- LCD screen display
- Supports one-touch arm (Arming without password)
- Supports fire/panic/medical alarm key
- Supports company name, phone number, time display
- Supports 2 on-board alarm inputs and 1 on-board alarm output
- Supports maximum 64 keyfobs

## ▪ Specification

Hardware features	DS-PK1-LRT-HWE	DS-PK1-LRT-HWB
Tag reader built in	1 built-in tag reader	
Serial port	1 TTL serial port	
Tamper-Proof	1 back-cover tamper-switch (Will be damaged when tamper triggered)	
Buzzer	1 on-board buzzer	
Function key	8 Function keys: Query, away arm, stay arm, disarm, alarm output, project, left, right	
RS-485	1 RS-485	
Alarm input	2 on-board alarm inputs	
Alarm output	1 on-board alarm output	
<b>Electrical characteristics</b>		
Power supply	DC 12 V	
Power consumption	Quiescent consumption: 0.984W @12 VDC power supply with 82mA current	Quiescent consumption: 0.972W @12 VDC power supply with 81mA current
	Max consumption: 1.32W @12VDC power supply with 110mA current	Max consumption: 1.33W @12VDC power supply with 111mA current
<b>Wireless transmission</b>		
RF frequency	868 MHz	433 MHz
<b>Display</b>		
Numeric key	0 to 9 , * , #	
Display screen	LCD screen	
Indicator	4 indicators and 1 backlight: (1) Power: Green (2) Faults: Fault-Orange / Alert-Flashing orange / Find me mode-flashing green (3) Armed: Blue (4) Alarm: Red (5) Keypad button backlight: White	
<b>General</b>		
Dimension(W×H×D)	150 mm × 115 mm × 28 mm	
Color	White	
Operation temperature	- 10 °C to 55 °C (14 °F to 131 °F)	
Operation humidity	10% to 90%	
<b>Device management</b>		
Keyfob	64	

## ORDERING INFORMATION

114-501

Hikvision DS-PK1-LRT-HWB Wired Keypad



Innovative Electronic Solutions  
www.ness.com.au



**NSW** Ph 02 8825 9222  
sales@ness.com.au

**VIC** Ph 03 9875 6400  
nessmelb@ness.com.au

**QLD** Ph 07 3399 4910  
nessbris@ness.com.au

**WA** Ph 08 9328 2511  
nessper@ness.com.au

**SA** Ph 08 8152 0000  
adelaide@ness.com.au